MINOR SUBDIVISION SURVEY FOR THE CODY SHINER MINOR SUBDIVISION N 89°56'34" W 5263.66' SECTION 8, TOWNSHIP 2 SOUTH, RANGE 3 WEST S 89'56'34" E SEC 5 SEC 4 1315.92' SEC 6 SEC 5 UINTAH SPECIAL BASE AND MERIDIAN SEC 8 SEC 9 1240.92' 1315.92' SEC 8 1315.92' FOUND COUNTY ALUMINUM PIPE DUCHESNE COUNTY, UTAH FOUND COUNTY ALUMINUM CAP AT AND CAP AT SECTION CORNER SECTION CORNER BOUNDARY DESCRIPTION Commencing at the Southwest Corner of Section 8, Township 2 South, Range 3 West of the Uintah Special Base Thence North 89°56'02" East 932.50 feet along the South line of the SW1/4 of the SW1/4 of said Section to the North right-of-way line of State Highway 87; Thence North 41°35'58" West 312.27 feet along said right-of-way line to the TRUE POINT OF BEGINNING; Thence North 41°35'58" West 1079.00 feet along said right-of-way line to the West line of said Section; SCALE: 1=300' NE1/4 NW1/4 Thence North 00°29'05" East 956.74 feet along said West line; Thence South 83°08'56" East 648.86 feet; NW1/4 Thence North 00°25'52" East 709.75 feet; Thence North 89'34'07" West 644.19 feet to the West Quarter Corner of said Section; Thence North 00'12'08" East 78.00 feet along the West line of the NW1/4 of said Section; Thence South 89'47'52" East 208.00 feet; Thence North 00°12'08" East 628.27 feet; Thence North 89°47'52" West 208.00 feet to said West line; Thence North 00°12'08" East 602.24 feet to the Southwest Corner of the NW1/4 of said NW1/4; Thence South 89°55'57" East 1315.21 feet to the Southeast Corner of said aliquot part; Thence North 00°13'58" East 1308.75 feet to the Northeast Corner of said aliquot part;
Thence South 89°56'34" East 75.00 feet along the North line of the NE1/4 of said NW1/4;
Thence South 04°20'45" East 1312.65 feet to the South line of said aliquot part;
Thence South 26°05'41" East 1458.30 feet to the South line of the SE1/4 of said NW1/4; Thence South 04°44'49" East 1529.01 feet to an existing rebar Thence South 01°10'05" East 1102.63 feet to the South line of the SE1/4 of said SW1/4; Thence South 89°43'33" West 992.09 feet to the Southeast Corner of said SW1/4 of said SW1/4; S 89'55'57" E 1315.21' 1315.21' 1135.43' 1315.21' Thence South 89°56'02" West 66.31 feet along said South line of said SW1/4 of said SW1/4 to a point in an S 89°55'57" E 5260.85' 882.90 existing roadway;
Thence North 53\*42'20" East 460.07 feet in said roadway;
Thence North 38\*45'58" East 148.76 feet in said roadway;
Thence North 23\*25'53" East 216.31 feet in said roadway;
Thence North 39\*51'34" East 45.67 feet to an existing fence corner; LEGEND AND NOTES Thence North 83°57'09" East 129.63 feet; Thence South 73°24'52" East 282.89 feet; LOT SET 5/8"X24" REBAR WITH CAP STAMPED ALLRED SURVEYING AT PROPERTY CORNERS Thence North 03°08'15" West 460.40 feet; 10.00 Acres Thence North 89°34'26" West 620.24 feet to a point in an existing roadway; O SET MAG NAIL WITH BRASS WASHER AT PROPERTY NOT A Thence North 05°10'24" East 102.65 feet; PROPOSED Thence North 35'20'58" East 196.28 feet to a monument spike in an existing roadway; BUILDING LOT Thence South 89°33'41" East 320.46 feet; Thence North 10°06'32" West 429.58 feet to a pipe fence corner; FOUND REBAR SET PREVIOUSLY AT PROPERTY CORNERS Thence North 08°07'19" West 405.97 feet to a pipe fence corner; N 89'47'52" W ▲ FOUND FENCE CORNER POST Thence South 79°44'39" West 517.88 feet to a gate post; 208.00 Thence South 34°22'56" West 18.09 feet to a pipe gate post; FOUND ALUMINUM CAP ON REBAR AT 1/16 CORNER Thence South 69'30'58" West 353.29 feet to a fence post in an East-West fence; NW1/4 A468 Thence South 12°06'56" West 979.23 feet to a rebar; FOUND MONUMENT SPIKE SET PREVIOUSLY PG292 Thence South 60°41'35" East 457.64 feet to a rebar; Thence South 48°22'39" West 690.16 feet to the TRUE POINT OF BEGINNING, containing 128.26 acres. Said parcel ---- EXISTING FENCES being subject all existing rights-of-ways and easements. FOUND HIGHWAY RIGHT-OF-WAY MARKERS THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM AN PROCEDURES AND EQUIPMENT. OWNER'S CERTIFICATE THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. We, the undersigned, owners of the parcels of land shown hereon, having caused the same to be subdivided into the parcels and right-of-way easements as shown, do hereby set apart the same as a minor subdivision, and FOUND COUNTY OBSERVATIONS AT A CONTROL POINT LOCATED AT LAT: 40°19'48.261" N AND LONG: 110°13'19.023" W USING THE UTAH STATE G.P.S. S 89°47,52" E ALUMINUM PIPE LOT 2 place the boundary lines of the parcels as shown and described on this plat. 208.00' AND CAP AT VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND (REMAINDER) QUARTER CORNER 487.96 OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER. 826.55 Date Acknowledged Notary's Landowner's Signatures 1314.51' N 89°34'07" W 644.19' S 89°55'19" E 5258.04' to Notary MARKER AT 1/4 CORNER AGRICULTURAL LOT NARRATIVE This survey was performed at the request of Cody Shiner for the purpose of locating on the ground the corners of the parcel shown and described on this plat and to divide off a ten acre lot, (Lot 1). This parcel is the remainder after the several parcels shown were conveyed off previously. The boundaries of these parcels were determined from their various deeds and previous surveys. Section 8 was originally surveyed by the General Land Office using the "3-mile" method in which the sixteenth corners were set. This section was subdivided by this survey using the "3-mile" method using the corners as found or reestablished as noted on the plat and is intended to represent a dependent resurvey of portions of Section 8 and is designed to restore the corners to their true original locations according to the best available evidence. Data from the plats of NW1/4 CEDAR POST previous surveys was obtained and used to determine the location of the existing corners of those parcels previously conveyed off. **ACKNOWLEDGMENT** State of Utah County of Duchesne \$SS On the dates shown by each signature, personally appeared before me the signers of the above certificate who duly acknowledged to me that they did execute same. My commission expires \_\_\_\_\_ Notary Public 1316.63 1316.62' 1316.63' 1316.63' DUCHESNE COUNTY TREASURER S 89°56'22" E 5266.52' S 89'33'41" E MONUMENT SPIKE AT CORNER PROPERTY TAX CLEARANCE SURVEYOR'S CERTIFICATE This is to certify that this plat was prepared from the field notes and electronic data collector files of an actual survey made by me, or under my personal supervision, of the parcels of land shown hereon, and that the THIS \_\_\_\_\_\_ OF 20\_\_\_\_. N 89°34'26" W REBAR AT ANGLE monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge. STEPHEN POTTER
DUCHESNE COUNTY TREASURER DUCHESNE COUNTY PLANNING DEPARTMENT APPROVAL EXISTING \_\_S APPROVED AS A MINOR SUBDIVISION ON Jerry D. Allred, Professional Land Surveyor THIS\_\_\_\_\_\_ OF 20\_\_\_\_ Certificate 148951 (Utah) MICHAEL HYDE DUCHESNE COUNTY COMMUNITY DEVELOPMENT DIRECTOR COUNTY RECORDER'S CERTIFICATE STATE OF UTAH COUNTY OF DUCHESNE }SS FOUND COUNTY ALUMINUM PIPE THIS IS TO CERTIFY THAT THIS PLAT WAS FILED FOR RECORD IN THE COUNTY RECORDER'S OFFICE ON THE AND CAP AT \_\_, 20\_\_\_, AT \_\_\_\_\_O'CLOCK \_\_M, AND IS DULY RECORDED. QUARTER CORNER SEC 8 SEC 9 SEC 7 \$\frac{1}{2} SEC 8 1314.40' FOUND ALUMINUM N 89°43'33" E 1325.94 SEC 17 \$ SEC 16 S 89°44'22" E 2628.84' S 89.56'02" W 1320.29' SEC 18 △ SEC 17 66.31' CAP ON REBAR AT FOUND 5/8" REBAR ON FOUND COUNTY COUNTY RECORDER FOUND COUNTY 1/16 CORNER PROPERTY LINE 0.20' ALUMINUM PIPE ALUMINUM CAP AT NORTH OF SECTION LINE AND CAP AT SECTION CORNER SECTION CORNER JERRY D. ALLRED & ASSOCIATES, INC. SURVEYING CONSULTANTS 1235 NORTH 700 EAST——P.O. BOX 975 DUCHESNE, UTAH 84021 (435) 738—5352 1 MAY 2017 17-100-020

County Surveyor's File# 3550